

# RUBADECK®

## Technical DATA



## Rubadeck® Retro Product Information

**EN 14041:2008**

### APPLICATION

Slip resistant decking upgrade.

### PRODUCT

Rubadeck Retro

### COLOURS

Woodland, Cinder, Slate.

### MATERIAL

Elastic pre manufactured flooring mat made from EPDM granulates and selected rubber granulates bound with polyurethane.

### THICKNESS

4mm

**Notice:** The above mentioned test data are based on periodical laboratory testing of test specimen taken from the actual manufacturing process and show the average values measured. The publishing of these technical data does not relieve the user of the necessity to test the relevant product for physical fitness based on a specific application. As the final use and application of our products are out of our control, this is the sole responsibility of the buyer / end user. All of our products do carry a warranty against manufacturer's defects according to our standard terms and conditions of sale. Due to deviations in raw materials, external influences like temperature and humidity variations, and the fact that this data relates to a resilient material, the above mentioned values are subject to vary up to +/- 25%.

## TECHNICAL DATA

### SPECIFIC WEIGHT

1060 kg/m<sup>3</sup>

### WEIGHT PER M2

4.24 kg

### TENSILE STRENGTH

2.20 N/mm<sup>2</sup> following DIN EN ISO 1798

### ELONGATION AT BREAK

105% following DIN EN ISO 1798

### TEAR RESISTANCE

13.5 N/mm following DIN ISO 34-1

### COEFFICIENT OF FRICTION

≥ 0,3 B EN 14 041

### TEMPERATURE RESISTANCE

- 40° C up to 115° C

### COEFFICIENT OF FRICTION

DIN EN 13 893



### FIRE RESISTANCE

DIN EN 13 501-1

